

## D5S.710A.SB.100 Europrofile anti-panic cylinder

---

### System-level description

---

### Feature summary

---

## Dimensional drawing

---

### Memory capacity

|                                 |     |
|---------------------------------|-----|
| Number of access rights.....    | 210 |
| Number of blocklisted keys..... | 500 |
| Number of time slots.....       | 10  |
| Size of event log .....         | 500 |

---

### Technical data

|                                                  |                              |
|--------------------------------------------------|------------------------------|
| Ingress protection rating.....                   | IP55                         |
| Long neck .....                                  | X                            |
| Real time clock battery lifetime .....           | 10 years                     |
| Real time clock compatibility.....               | One real time clock included |
| Remote management with iLOQ Online products..... | X                            |

---

### Certificates

|                                                       |         |
|-------------------------------------------------------|---------|
| Attack resistance (EN 15684:2020).....                | Grade D |
| Category of use (EN 15684:2020).....                  | Grade 1 |
| Credential related security (EN 15684:2020).....      | Grade D |
| Durability (EN 15684:2020).....                       | Grade 6 |
| Environmental resistance (EN 15684:2020) .....        | Grade 4 |
| Fire/smoke resistance (EN 15684:2020).....            | Grade B |
| Mechanical key related security (EN 15684:2020) ..... | Grade 0 |
| System management (EN 15684:2020) .....               | Grade 2 |