Life made limitless.

# D5S.710A.SB.80 Europrofile anti-panic cylinder

## System-level description

## Feature summary

iLOQ Oy • Oulu, Finland • www.iLOQ.com • iLOQ is registered trademark of iLOQ Oy •
©2024 iLOQ Oy. All Rights Reserved •

## Dimensional drawing

## Memory capacity

| | |
|---|---|
| Number of access rights | 210 |
| Number of blocklisted keys | 500 |
| Number of time slots | 10 |
| Size of event log | 500 |

## Technical data

| | |
|---|---|
| Ingress protection rating | IP55 |
| Long neck | ✗ |
| Real time clock battery lifetime | 10 years |
| Real time clock compatibility | One real time clock included |
| Remote management with iLOQ Online products | ✗ |
| Maximum temperature | 70°C |
| Minimum temperature | -25°C |
| Attack resistance (EN 15684:2020) | Grade D |
| Category of use (EN 15684:2020) | Grade 1 |
| Credential related security (EN 15684:2020) | Grade D |
| Durability (EN 15684:2020) | Grade 6 |
| Environmental resistance (EN 15684:2020) | Grade 4 |
| Fire/smoke resistance (EN 15684:2020) | Grade B |
| Mechanical key related security (EN 15684:2020) | Grade 0 |
| System management (EN 15684:2020) | Grade 2 |

iLOQ Oy • Oulu, Finland • www.iLOQ.com • iLOQ is registered trademark of iLOQ Oy •
©2024 iLOQ Oy. All Rights Reserved •