

SKG-IKOB PRODUCTCERTIFICATE

514.392.01

Date of issue: 27-02-2024



Certificate holder

iLOQ Oy
Elektronikkatie 10
FI-90590 Oulu
T: +358 (0) 40 3170 200
E: info@iloq.com
I: www.iloq.com



Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

electro mechanical euro cylinder

delivered under logo / brand:

iLOQ

delivered under type- and / or article number:

D5S.100A.SB , D5S.110A.SB
D5S.200A.SB , D5S.210A.SB , D5S.220A.SB
D5S.400A.SB , D5S.410A.SB
D5S.500A.SB , D5S.510A.SB
D5S.700A.BS.xx , D5S.710A.SB.xx
xx = length of the cylinder

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, appearing to be "H.A.J. van Dartel", written over a light blue horizontal line.

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

CERTIFICATE

SKG-IKOB PRODUCTCERTIFICATE

iLOQ Oy
Number: 514.392.01

page 2 of 2

1. PRODUCT

electro mechanical euro cylinder

PRODUCT TYPE

cylinder

2. TECHNICAL SPECIFICATION

Operating:	Electronical operation
Construction:	modular single with a lockable rotary knob modular double with on both sides a lockable rotary knob
System:	round key profile, 1 electronic operated detainer, self-generating power
Material:	cylinder body: stainless steel with various coating
Dimension:	17 mm profile from: (single) 10/30 mm in various extensions per 0/5 mm and (double) 30/30 mm in various extensions per 5 mm
Fixing:	1 steel bolt M5, length \geq backset + 10 mm
Intended use:	in combination with cylinder mortice locks and security furnitur

3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:

NL_20200630

4. PERFORMANCES

A electro mechanical euro cylinder according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this electro mechanical euro cylinder is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this electro mechanical euro cylinder is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).
