

## D5S.710A.SB.75 Europrofile anti-panic cylinder

---

### System-level description

---

### Feature summary

Memory capacity

|                                 |     |
|---------------------------------|-----|
| Number of access rights.....    | 210 |
| Number of blocklisted keys..... | 500 |
| Number of time slots.....       | 10  |
| Size of event log .....         | 500 |

Technical data

|                                                       |                              |
|-------------------------------------------------------|------------------------------|
| Ingress protection rating.....                        | IP55                         |
| Long neck .....                                       | X                            |
| Real time clock battery lifetime .....                | 10 years                     |
| Real time clock compatibility.....                    | One real time clock included |
| Remote management with iLOQ Online products.....      | X                            |
| Maximum temperature .....                             | 70°C                         |
| Minimum temperature.....                              | -25°C                        |
| Attack resistance (EN 15684:2020).....                | Grade D                      |
| Category of use (EN 15684:2020).....                  | Grade 1                      |
| Credential related security (EN 15684:2020).....      | Grade D                      |
| Durability (EN 15684:2020).....                       | Grade 6                      |
| Environmental resistance (EN 15684:2020) .....        | Grade 4                      |
| Fire/smoke resistance (EN 15684:2020).....            | Grade B                      |
| Mechanical key related security (EN 15684:2020) ..... | Grade 0                      |
| System management (EN 15684:2020) .....               | Grade 2                      |