SKG-IKOB PRODUCTCERTIFICATE 514.392.02

Date of issue: 02-02-2026

Certificate holder
iLOQ Oy
Elektroniikkatie 10
FI-90590 Oulu
T: +358 (0) 40 3170 200
E: info@iloq.com
I: www.iloq.com

CERTIFICATE

Declaration of SKG-IKOB
This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

europrofile cylinder with non lockable knob electro mechanical

delivered under logo / brand:

iLOQ

delivered under type- and / or article number:

D5S.300A.SB , D5S.310A.SB

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

1. PRODUCT
europrofile cylinder with non lockable knob electro mechanical

PRODUCT TYPE
cylinder

2. TECHNICAL SPECIFICATION

Operating:	Mechanical and electronical operation
Construction:	modular single parts, with on both sides a rotary knob
	1 side lockable, with OR without panic function
System:	round key profile
	1 electronic operated detainer, self-generating power
	operation by: - NFC-Key
Material:	cylinder body: stainless steel with various coatings
Dimension:	17 mm profile from 30/30 mm in various extentions per 5 mm
Fixing:	1 steel bolt M5, length ≥ backset + 10 mm
Intended use:	The electromechanical product is operated electronically by means of the options as mentioned under "System".
	The operating options mentioned below, as well as the lock, are included in the[nr Self-declaration - additional product requirements for electromechanical and
	electronic Hinges and Locks; dated 28-01-2026, with which the certificate holder declares
	that the applicable requirements are met.
	in combination with cylinder mortice locks and security furniture.
	Pay Attention:
	This cylinder achieves only the SKG-star rating if a door element (including side window),
	wherein at least P4A laminated glass has been applied, OR
	in a door element (including side window) with a section filling without a view on the knob.
	A wooden door element (including side window) with a view to the "standard"
	turning knob, should be provided with a SKG (V) certified anti-drill / manipulation device.

3. DELIVERY
The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:
D5S - REV_2_1_160125

4. PERFORMANCES
A europrofile cylinder with non lockable knob electro mechanical according this certificate fulfils the relevant requirements of BRL 3104.
A window- or door set, in which this europrofile cylinder with non lockable knob electro mechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this europrofile cylinder with non lockable knob electro mechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).