SKG-IKOB PRODUCTCERTIFICATE 514.392.01

Date of issue: 02-02-2026

Certificate holder
iLOQ Oy
Elektroniikkatie 10
FI-90590 Oulu
T: +358 (0) 40 3170 200
E: info@iloq.com
I: www.iloq.com

CERTIFICATE

Declaration of SKG-IKOB
This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

electro mechanical euro cylinder

delivered under logo / brand:

iLOQ

delivered under type- and / or article number:

D5S.100A.SB , D5S.110A.SB
D5S.200A.SB , D5S.210A.SB , D5S.220A.SB
D5S.400A.SB , D5S.410A.SB
D5S.500A.SB , D5S.510A.SB
D5S.700A.BS.xx, D5S.710A.SB.xx
xx = length of the cylinder

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

ir. H.A.J. van Dartel
Certification manager

Verify at www.sterrenwijzer.nl if this certificate is still valid and actual.
This certificate contains 2 pages.

SKG-IKOB Certificatie
Poppenbouwing 56
4191 NZ Geldermalsen

Postbus 202
4190 CE Geldermalsen

T 088-2440100
info@skgikob.nl
www.skgikob.nl

1. PRODUCT
electro mechanical euro cylinder

PRODUCT TYPE
cylinder

2. TECHNICAL SPECIFICATION

Operating:	Electronical operation
Construction:	modular single with a lockable rotary knob
	modular double with on both sides a lockable rotary knob
System:	round key profile, 1 electronic operated detainer, self-generating power
	operation by: - NFC-Key
Material:	cylinder body: stainless steel with various coating
Dimension:	17 mm profile from:
	(single) 10/30 mm in various extensions per 0/5 mm and
	(double) 30/30 mm in various extensions per 5 mm
Fixing:	1 steel bolt M5, length ≥ backset + 10 mm
Intended use:	The electromechanical lock version of this product certificate only achieves the burglary-resistant performance, when the control/operating options are applied, as stated under "System".
	By means of the Self-declaration - additional product requirements for electromechanical and electronic Hang- en Sluitwerk; dd. 28-01-2026, the certificate holder declares that the requirements are only met in this way.
	in combination with cylinder mortice locks and security furnitur

3. DELIVERY
The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:
D5S - REV_2_1_160125

4. PERFORMANCES
A electro mechanical euro cylinder according this certificate fulfils the relevant requirements of BRL 3104.
A window- or door set, in which this electro mechanical euro cylinder is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

- the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this electro mechanical euro cylinder is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

- the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).